



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 228 731 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
07.08.2002 Bulletin 2002/32

(51) Int Cl.⁷: **A47J 37/12**

(21) Application number: **02075393.5**

(22) Date of filing: **31.01.2002**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **van Ratingen, Joseph**
3500 Hasselt (BE)

(74) Representative: **Debrabandere, René**
Bureau De Rycker nv
Arenbergstraat 13
2000 Antwerpen (BE)


(30) Priority: **02.02.2001 BE 200100081**

(71) Applicant: **van Ratingen, naamloze vennootschap**
3500 Hasselt (BE)

(54) **Electric deep fat fryer**

(57) The invention relates to an electric deep fat fryer, comprising a vessel (1) and an immersion resistor (2) with a heating part (3) which is situated in the vessel (1) at a small distance from the bottom (1A) of the vessel

(1), and a connection part (4,5) connecting the heating part (3) to a thermostat, the sensor (17) of which is situated in the vessel (1). The sensor (17) of the thermostat is situated at a distance above the lowermost-situated part of the heating part (3) of the immersion resistor (2).



EP 1 228 731 A1

Description

[0001] This invention relates to an electric deep fat fryer with the principle of the "cold zone", which comprises a vessel and an immersion resistor with a heating part which is situated in the vessel at a small distance from the bottom of the vessel, and a connection part connecting the heating part to a thermostat, the sensor of which is situated in the vessel.

[0002] By means of the regulating part of the thermostat and an on- and off-switch, situated in a switch box, the immersion resistor is supplied with power.

[0003] In consideration of the fact that usually the immersion resistor, together with the thermostat, can be removed from the vessel, the sensor of the thermostat mostly is mounted on this immersion resistor, between two parts of the heating part.

[0004] With known electric deep fat fryers, this heating part extends almost in one plane, and the sensor of the thermostat is situated in this same plane.

[0005] It has been noted that the heating of the frying oil with such deep fat fryers is not optimum.

[0006] The sensor is influenced by the temperature in the "cold" zone, this is the zone situated in the vessel beneath the heating part. In this zone, the frying oil, during frying, remains colder than thereabove, although the temperature in fact can rise up to 160°C.

[0007] The sensor does not react to the heating of the frying oil above the "cold" zone in an optimum manner.

[0008] The invention aims at an electric deep fat fryer which remedies said disadvantages and, with the same capacity of the immersion resistor, allows for a faster heating and a shorter frying process.

[0009] According to the invention, this aim is achieved in that the sensor of the thermostat is situated at a distance above the lowermost-situated part of the heating part of the immersion resistor.

[0010] Surprisingly, it was noted that, in comparison to an immersion resistor with the same capacity, however, with the sensor in the plane of a flat heating part, a 15 to 40% shorter frying process was obtained.

[0011] Preferably, the heating part of the immersion resistor comprises parts which are situated at different heights in respect to the bottom of the vessel, and the sensor of the thermostat is attached to a part of the heating part which is situated higher than the lowermost part.

[0012] In this case, the sensor of the thermostat may be provided, for example, together with the sensor of a safety system which protects the immersion resistor against excessive heating.

[0013] The lowermost-situated part of the heating part of the immersion resistor preferably is situated at a distance of 5 to 15 mm from the bottom of the vessel.

[0014] With such positioning, the cold zone seemed to be quieter and not so cold, as a result of which possible water droplets were vaporized before they could reach the bottom of the vessel, such that on the bottom, no accumulation up to large water droplets could take

place.

[0015] In the classical electric deep fat fryers, the heating part is situated at 25 mm or more from the bottom of the vessel. It was noted that with such deep fat fryers, a dangerous splashing of the frying oil may occur.

[0016] The products to be fried, for example, cut potatoes, which are brought into the deep fat fryer in a basket, however, contain an amount of water, a part of which is set free in the oil during the possible pre-frying as well as during the final frying.

[0017] As the specific weight of water is larger than that of oil, this water will sink and will accumulate below, in the cold zone. There, the water may accumulate up to relatively large drops which, when the temperature, during frying, rises in the cold zone, up to a value of even 160°C, are transformed into steam.

[0018] In particular when the temperature in the cold zone rises above 150°C, the mass of steam suddenly will rise upward through the oil, as a gas bubble, with a force which will cause the oil to splash.

[0019] In the deep fat fryer according to the invention, the heating part of the immersion resistor, as usual, may form a loop, however, this loop preferably does not extend in a plane parallel to the bottom. It comprises parts which are situated higher than others.

[0020] In consideration of the fact that the resistor must deliver a certain capacity, whereas the bottom surface of the vessel is limited, the loop in the known fryers mostly does not form a simple figure, but, for example, a loop with two or more adjacent U-shaped paths, with the bottom removed from the upward portions.

[0021] Whereas with known deep fat fryers, the portions forming a U-shaped path are parallel to the bottom of the vessel, according to the invention the heating element preferably also forms a loop comprising two or more adjacent loop portions which extend according to a U-shaped path and which, thus, each comprise two legs, whereby, however, loop portions or legs of loop portions are situated at different heights in respect to the bottom of the vessel and the sensor is attached to one or more higher-situated legs of loop portions.

[0022] With the intention of better showing the characteristics of the invention, hereafter, as an example without any limitative character, a preferred form of embodiment of an electric deep fat fryer according to the invention is described, with reference to the accompanying drawings, wherein:

Figure 1 schematically represents an electric deep fat fryer according to the invention, with cut-off vessel;

Figure 2 represents a perspective top view of the immersion resistor with sensor from the deep fat fryer of figure 1;

Figure 3 represents a perspective view of the side of the immersion resistor from the deep fat fryer of figure 1;

Figures 4 and 5 represent perspective views anal-

ogous to that of figure 2, however, relating to two other forms of embodiment of the invention.

[0023] The electric deep fat fryer with the principle of "cold zone" represented in figure 1 substantially consists of a vessel 1, a removable electric immersion resistor 2 installed therein at a distance from the bottom 1A of the vessel 1.

[0024] Possibly, a filter cover can be provided on the vessel 1.

[0025] In the represented example, the vessel 1 is an inner vessel of metal which further is surrounded by an outer vessel or mantle, which, for simplicity's sake, is not represented in figure 1.

[0026] On the mantle, a switch box, also not represented, is attached for connecting the power supply which, amongst others, comprises an on- and off-switch and a thermostat.

[0027] The immersion resistor 2, which in figures 2 and 3 is represented separately, consists of a heating part 3 forming a loop, the two extremities of which connect to two connection legs 4 and 5 of a connection part, extending adjacent to each other in upward direction, which are bent outward at the top of the vessel 1 and comprise connecting pins 6 at their extremity, with which pins they are connected to the power supply in the switch box.

[0028] The heating part 3 comprises two loop parts 7 and 8 situated next to each other which extend according to a U-shaped path and, thus, comprise two straight legs 9 and 10; 11 and 12. The loop parts 7 and 8 are symmetrical in respect to each other.

[0029] The inner legs 9 and 11 of these loop parts 7 and 8 connect with one extremity to the connection legs 4 and 5, respectively.

[0030] With its other extremity, the inner leg 9, by means of a rounded connection 13, is connected to an extremity of the outer leg 10 of the loop part 7, whereas the inner leg 11 with its other extremity, by means of a rounded connection 14, connects to an extremity of the outer leg 12.

[0031] The connections 13 and 14 do not only provide for a lateral distance between the legs 9 and 10, 11 and 12, respectively, but also for a distance therebetween in height direction, as, first of all, can be seen in figures 1 and 3. The outer legs 10 and 12 thus form parts which are situated lower, for example, between 1 and 2 cm lower, and, for example, approximately 1,5 cm lower, than the inner legs 9 and 11.

[0032] At the side of the connection legs 4 and 5, the loop 3 has a connection part 15 between the extremities of the outer legs 10 and 12. This connection part 15, too, thus is situated lower than the legs 9 and 11 and at the same distance from the bottom 1A of the vessel 1 as the outer legs 10 and 12 which are approximately parallel to this bottom 1A.

[0033] The distance from the bottom 1A on which these lowermost-situated parts, in the aforementioned

example, the legs 10 and 12 and the connection part 15, are situated, is 5 to 15 mm, preferably 10 to 15 mm and, for example, 12 mm.

[0034] The inner legs 9 and 11 are retained at a fixed distance from each other by means of a clamping piece 16 in which also the sensor 17 of the thermostat and the sensor 18 of a safety element against overheating of the heating part 3 are clamped. Thus, both sensors 17 and 18 are situated approximately at the height of the legs 9 and 11 in respect to the bottom 1A.

[0035] In this way, the sensor 17 is situated higher than the lowermost legs 10 and 12 and the connection part 15, such that, when the immersion resistor 2 is heating the oil in the vessel 1, a portion of the oil under the sensor 17 is heated. Thus, the sensor 17 is situated in heated oil and is not or little influenced by the temperature in the cold zone under the legs 10, 12 and the connection part 15.

[0036] As a consequence, the sensor 17 can work optimally and the amount of oil which is heated is larger, which results in a 15 to 40% shorter frying process than with a classical immersion resistor with a flat loop of the same capacity.

[0037] Further, the cold zone, in particular due to the positioning of the lowermost parts in the proximity of the bottom 1A of the vessel 1, is calmer and there is less danger for splashing as a result of water bubbles in the cold zone.

[0038] In a variant, not the inner legs 9 and 11 are connected to the connection legs 4 and 5, but the outer legs 10 and 12, whereas the inner legs 9 and 11 are connected to each other next to the connection legs 4 and 5, by means of a rounded connection. The outer legs 10 and 12 remain situated lower than the inner legs 9 and 11, and the sensor 17 also is attached to the inner legs 9 and 11.

[0039] Another variant of the immersion resistor 2 is represented in figure 4. The heating part 3 of the immersion resistor 2 forms a loop with three loop parts 19, 20 and 21, each extending according to a U-shaped path.

[0040] In this variant, all loop parts 19, 20 and 21 are approximately parallel to the bottom 1A of the vessel 1, however, the two outer loop parts 19 and 21 are situated lower and, therefore, more in the proximity of the bottom 1A of the vessel 1 than the central loop part 20.

[0041] The sensor 17 is provided between the legs of this central loop part 20.

[0042] In figure 5, still another variant is represented in which the heating part 3 of the immersion resistor comprises four loop parts 22, 23, 24 and 25 situated next to each other.

[0043] The most outwardly situated legs 26 and 27 of two outer loop parts 22 and 25 are situated higher than the other two legs 28 and 29 of these loop parts 22 and 25, whereas the most inwardly situated legs 30 and 31 of the remaining loop parts 23 and 24 are situated higher than the most outwardly situated legs 32 and 33 of these loop parts 23 and 24.

[0044] The sensor 17 is attached to the most inwardly and thus higher situated legs 30 and 31 of the two most inwardly situated loop parts 23 and 24 and is situated at the height of these legs 30 and 31.

[0045] It is obvious that the immersion resistor can adapt many other forms. Such, it may comprise parts at more than two different heights above the bottom of the vessel, for example, on three levels. It is important that the sensor 17 is not attached on the lowermost part, but thereabove, whereby this lowermost part preferably is situated at a distance between 5 and 15 cm from this bottom.

[0046] The invention is in no way limited to the form of embodiment described heretofore and represented in the figures, however, such deep fat fryer can be realized in different variants without leaving the scope of the invention.

Claims

1. Electric deep fat fryer, comprising a vessel (1) and an immersion resistor (2) with a heating part (3) which is situated in the vessel (1) at a small distance from the bottom (1A) of the vessel (1), and a connection part (4,5) connecting the heating part (3) to a thermostat, the sensor (17) of which is situated in the vessel (1), **characterized in that** the sensor (17) of the thermostat is situated at a distance above the lowermost-situated part of the heating part (3) of the immersion resistor (2).
2. Electric deep fat fryer according to claim 1, **characterized in that** the heating part (3) of the immersion resistor (2) comprises parts which are situated at different heights in respect to the bottom of the vessel, and that the sensor (17) of the thermostat is attached to a part (9,11;20;26,27) of the heating part (3) which is situated higher than the lowermost part.
3. Electric deep fat fryer according to claim 1 or 2, **characterized in that** the lowermost-situated part (10,12,15;19,21;28,29,32,33) of the heating part (3) of the immersion resistor (2) is situated at a distance of 5 to 15 mm from the bottom (1A) of the vessel (1).
4. Electric deep fat fryer according to any of the preceding claims, **characterized in that** the heating part (3) forms a loop.
5. Electric deep fat fryer according to claims 2 and 4, **characterized in that** the heating part (3) forms a loop having parts (9,11;20,26,27,30,31) which are situated higher than others (10,12,15;19,21;28,29,32,33).
6. Electric deep fat fryer according to claim 5, **characterized in that** the heating part (3) forms a loop

comprising at least two adjacent loop parts (7,8;19,20,21;22-25) which extend according to a U-shaped path and which, thus, each comprise two legs (9,10;11,12;26-31), whereby, however, loop parts (7,8;19-21;22-25) or legs (9,10,11,12;26-31) of loop parts (7,8;19-21;22-25) are situated at different heights in respect to the bottom (1A) of the vessel (1) and the sensor (17) is attached to one or more higher-situated legs (9,11;30,31) of loop parts and preferably is situated at approximately the same height as these legs.




Fig. 1




Fig. 2






Fig. 3





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 07 5393

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 4 058 703 A (PRICE GEORGE M) 15 November 1977 (1977-11-15) * column 2, line 9 - column 4, line 13; figures 1-5 *	1-5	A47J37/12
X	EP 0 133 906 A (PATZNER GMBH & CO) 13 March 1985 (1985-03-13) * page 1 - page 3; claims 1,2; figures *	1,2,4-6	
X	US 4 503 320 A (POLSTER LOUIS S) 5 March 1985 (1985-03-05) * column 2, line 61 - column 4, line 37; figures *	1,3	
X	US 3 998 146 A (PRICE GEORGE M) 21 December 1976 (1976-12-21) * column 2, line 24 - column 3, line 9; figures 1-3 *	1	
A	US 3 134 008 A (FINN JOHN J) 19 May 1964 (1964-05-19) * column 1, line 47 - column 2, line 14; figure 1 *	1,2	TECHNICAL FIELDS SEARCHED (Int.Cl.7) A47J H05B
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 15 April 2002	Examiner De Terlizzi, M
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (P04G01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 07 5393

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-04-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4058703	A	15-11-1977	US 3870859 A	11-03-1975
			CA 1025510 A1	31-01-1978
			CA 1039785 A2	03-10-1978
			DE 2510232 A1	02-01-1976
			FR 2274257 A1	09-01-1976
			GB 1515364 A	21-06-1978
			GB 1515365 A	21-06-1978
			JP 1040268 C	31-03-1981
			JP 51007163 A	21-01-1976
			JP 55033331 B	30-08-1980
			NL 7502833 A ,B,	19-12-1975
			US 3938498 A	17-02-1976
EP 0133906	A	13-03-1985	DE 3323605 A1	10-01-1985
			AT 32942 T	15-03-1988
			DE 3469798 D1	14-04-1988
			EP 0133906 A1	13-03-1985
			FI 842634 A ,B,	31-12-1984
			NO 842606 A ,B,	02-01-1985
US 4503320	A	05-03-1985	NONE	
US 3998146	A	21-12-1976	US 3911250 A	07-10-1975
			US 4032749 A	28-06-1977
US 3134008	A	19-05-1964	NONE	

EPO FORM PC455

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82